


PROPERTY SURVEY FOR
ALTON MOON
 SECTION 27 TOWNSHIP 1 NORTH, RANGE 9 WEST
 UTAH SPECIAL BASE AND MERIDIAN



PARCEL A
 Beginning at a point which is South 33°00'43" East 2311.72 feet from the West Quarter Corner of Section 27, Township 1 North, Range 9 West of the Uintah Special Base and Meridian, the basis of bearings being a bearing of South 00°06'13" East from the Northwest Corner of said Section to said Quarter Corner;
 Thence North 90°00'00" East 454.25 feet to the centerline of an existing wash;
 Thence the following nine courses along said centerline:
 South 14°31'40" East 134.87 feet;
 South 39°26'22" East 98.00 feet;
 South 05°22'11" East 54.53 feet;
 South 57°23'21" East 108.57 feet;
 South 10°06'32" East 54.81 feet;
 South 39°14'43" East 131.84 feet;
 South 05°09'28" East 63.65 feet;
 South 33°50'07" East 117.91 feet;
 South 13°53'57" West 48.56 feet to the South line of said Section 27;
 Thence South 89°40'17" West 799.66 feet along said South line;
 Thence North 00°00'00" East 688.17 feet to the Point of Beginning, containing 10.00 acres.
 TOGETHER WITH a twenty feet (20') wide road right-of-way over an existing road to State Highway 35.

PARCEL B
 Beginning at a point which is South 33°00'43" East 2311.72 feet from the West Quarter Corner of Section 27, Township 1 North, Range 9 West of the Uintah Special Base and Meridian, the basis of bearings being a bearing of South 00° East from the Northwest Corner of said Section to said Quarter Corner;
 Thence South 00°00'00" West 688.17 feet to the South line of said Section 27;
 Thence South 89°40'17" West 1259.33 feet along said South line to the Southwest Corner of said Section;
 Thence North 00°00'11" West 685.39 feet along the West line of said Section;
 Thence North 90°00'00" East 1259.35 feet to the Point of Beginning, containing 20.00 acres.
 TOGETHER WITH a twenty feet (20') wide road right-of-way over an existing road to State Highway 35.

NARRATIVE
 This survey was performed at the request of Alton Moon for the purpose of describing the two parcels shown on this plat. The corners indicated were found as shown and used to control the survey.


THIS SURVEY WAS PERFORMED USING GLOBAL POSITIONING SYSTEM (G.P.S.) PROCEDURES AND EQUIPMENT. THE BEARINGS ARE BASED ON WGS 84 DATUM.

SURVEYOR'S CERTIFICATE
 This is to certify that I have surveyed the parcels of land shown on this plat, and that the monuments indicated were found or set during said survey, and that this plat accurately represents said survey to the best of my knowledge.



Jerry D. Allred, Registered Land Surveyor,
 Certificate No. 148951, (Utah)

COUNTY SURVEYOR'S FILE # 1265



11 DEC 2002 02-100-081

SEC 21 SEC 22
 SEC 28 SEC 27

FOUND ORIGINAL STONE AND MOUND SET BY 1898 AT SECTION CORNER

S 00°06'13" E
 2648.30'

FOUND ORIGINAL MARKED STONE SET BY COUNTY MONUMENT FOR 7/4 CORNER

S 00°00'11" E 1328.60'
 S 00°00'11" E 2633.90'

S 33°00'43" E
 2311.72'

STATE HIGHWAY 35

▲
 BASE

20' WIDE ROAD RIGHT-OF-WAY ALONG AN EXISTING ROAD

N 90°00'00" E 1259.35'
 N 90°00'00" E 454.25'

LINE TABLE			
L1	S 14°31'40" E	134.87'	
L2	S 39°26'22" E	98.00'	
L3	S 05°22'11" E	54.53'	
L4	S 57°23'21" E	108.57'	
L5	S 10°06'32" E	54.81'	
L6	S 39°14'43" E	131.84'	
L7	S 05°09'28" E	63.65'	
L8	S 33°50'07" E	117.91'	
L9	S 13°53'57" W	48.56'	

20.00 ACRES

10.00 ACRES

SEC 28 SEC 27
 SEC 33 SEC 34

S 89°40'17" W 1259.33'
 S 89°40'17" W 799.66'

OLD EXISTING FENCE ALONG SECTION LINE

FOUND OLD CORNER POST AT SECTION CORNER