

# DUCHESNE COUNTY MONUMENT SURVEY RECORD

T1S R7W



SEC 30

1/4 ———

SEC 31

U.S.B.&M.

E-3



N 89°53'45" E  
1327.66'

N 89°48'17" E

SECTION CORNER

1324.62'

1/16 CORNER



SCALE: 1"=30'

NOTE:  
THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT LOCATED AT LAT: 40°21'07.23762"N AND LONG: 110°42'37.33941"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER

## DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND B.L.M. ALUMINUM CAP ON A 5/8" REBAR AT POSITION OF CORNER



## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

REFERENCED AS SHOWN

STATE PLANE COORDINATE DATA  
(U.S. STATE PLANE)  
NAD 83 UTAH CENTRAL ZONE  
7301010.061  
1860885.056

LATITUDE: 40°21'37.72859" N

LONGITUDE: 110°42'31.81756" W

PUBLIC LAND SURVEY SYSTEM GCDB ID NO. U7300010S0070W0\_104200

## CERTIFICATION

I, Jerry D. Allred, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date 27 Sep 2010

Jerry D. Allred, Professional Land Surveyor  
Certificate No. 148951  
Duchesne County Surveyor

