


SAFCO PRODUCTS • NEW HOPE, MINNESOTA REPRODUCED BY PART NUMBER 6551

SEC 35 SEC 36 S 89°48'47" E 1309.37' S 89°48'06" W 1313.24'
 SEC 2 SEC 1

POSITION OF SECTION CORNER DETERMINED FROM BLM DATA

FOUND GALVANIZED PIPE AND CAP AT 1/16 CORNER



SCALE: 1"=400'



PROPERTY SURVEY FOR
HOWARD JENKINS
 SECTION 1, TOWNSHIP 2 SOUTH, RANGE 3 WEST
 UTAH SPECIAL BASE & MERIDIAN

DESCRIPTION OF PARCEL


All of the Southeast Quarter of the Southwest Quarter of Section 1, Township 2 South, Range 3 West of the Uintah Special Base and Meridian, said parcel being further described as follows:
 Beginning at the South Quarter Corner of said Section 1;
 Thence South 88°24'14" West 1335.35 feet to the Southwest Corner of said Southeast Quarter;
 Thence North 00°38'35" East 1359.71 feet to the Northwest Corner of said Southeast Quarter;
 Thence North 89°37'49" East 100.99 feet along the North line of said Southeast Quarter to the South right-of-way line of the County Road;
 Thence Easterly 1077.77 feet along said right-of-way line on a curve to the left, said curve having a central angle of 86°07'30" and a radius of 717.00 feet with a chord which bears South 73°07'43" East 979.13 feet;
 Thence North 62°30'53" East 319.51 feet along said South right-of-way line to the East line of said Southeast Quarter;
 Thence South 00°05'23" West 1186.37 feet along said East line to the Point of Beginning, containing 33.5 acres.

NARRATIVE

This survey was performed at the request of Howard Jenkins for the purpose of determining the area of the SE 1/4 of the SW 1/4 of Section 1 which lies South of the County Road. This section was resurveyed by the Bureau of Land Management in 2002 and several monuments set by that survey were found and used to control this survey.

SURVEYOR'S CERTIFICATE

This is to certify that I have surveyed the parcel of land shown on this plat, and that the monuments indicated were found or set during said survey, and that this plat accurately represents said survey to the best of my knowledge.



15 Aug 2005
 Jerry D. Allred, Professional Land Surveyor,
 Certificate No. 148951, (Utah)

S 00°13'59" W 5284.56'

POSITION OF CORNER DETERMINED FROM BLM DATA

COUNTY ROAD

POSITION OF CORNER DETERMINED FROM BLM DATA

S 89°37'49" W 1321.67' 2643.35' 1321.67' 100.99'
 A=1077.77' R=717.00' Δ=86°07'30"
 N 62°30'53" E 319.51'

FOUND BLM MONUMENT AT 1/16 CORNER

POSITION OF SECTION CORNER DETERMINED FROM WITNESS

N 00°38'35" E 1359.71' 144.59' 1330.96' 1186.37'
 SE 1/4 SW 1/4 33.50 ACRES
 FOUND BLM MONUMENT AT 1/16 CORNER FOUND BLM MONUMENT AT 1/4 CORNER

SEC 2 SEC 1 N 88°07'14" W 1312.41'
 SEC 11 SEC 12 1335.35'

FOUND BLM MONUMENT AT WITNESS CORNER

COUNTY SURVEYOR FILE NO. 1648

JERRY D. ALLRED AND ASSOCIATES
 SURVEYING CONSULTANTS
 121 NORTH CENTER ST.--P.O. BOX 975
 DUCHESNE, UTAH 84021
 (435) 738-5352