




DUCHESNE COUNTY MONUMENT SURVEY RECORD

T3S R2W
 SEC 29 — SEC 28
 S 1/16
 U.S.B.&M.



NOTE:
 THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (N 1/16 CORNER SEC. 21) LOCATED AT LAT: 40°12'40.14273"N AND LONG: 110°06'51.09603"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER.



NO SCALE

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND 2½" G.L.O. BRASS CAP AT THE SOUTH 1/16 CORNER BETWEEN SECTIONS 29 AND 28.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

REFERENCED AS SHOWN.

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)
 NAD 83 UTAH CENTRAL ZONE
 N: 7240639.106
 E: 2024895.558

LATITUDE: 40°11'21.510"N

LONGITUDE: 110°07'25.266"W


PUBLIC LAND SURVEY SYSTEM GCDB ID NO. UT300030S0020W0_300220

CERTIFICATION

I Jerry D. Allred, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date 14 Nov 2011

Jerry D. Allred, Professional Land Surveyor
 Certificate No. 148951
 Duchesne County Surveyor



SCANNED 14 Nov 2011