



DUCHESNE COUNTY MONUMENT SURVEY RECORD

T3S R7W
 SEC 23 | SEC 24
 1/4
 U.S.B.&M.




NO SCALE

NOTE:
 THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT: 40°11'52.73389"N AND LONG: 110°34'39.74986"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER.

DESCRIPTION OF CORNER EVIDENCE FOUND


FOUND ROLLED PIN IN MOUND OF STONES AT THE POSITION OF THE 1/4 CORNER, ALONG WITH TWO BEARING TREES.



DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

RESET A 5/8" REBAR WITH A 1 1/2" ALUMINUM CAP AT THE POSITION OF THE CORNER.

REFERENCED AS SHOWN.



STATE PLANE COORDINATE DATA
 (U.S. SURVEY FEET)
 NAD 83 UTAH CENTRAL ZONE
 N: 7244622.568
 E: 1882373.722


LATITUDE: 40°12'18.532"N
LONGITUDE: 110°38'01.282"W
PUBLIC LAND SURVEY SYSTEM GCDB ID NO. UT300030S0070W0_600340

CERTIFICATION

I, Jerry D. Allred, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date 14 Nov 2011

Jerry D. Allred, Professional Land Surveyor
 Certificate No. 148951
 Duchesne County Surveyor



SCANNED 15 Nov 2011